WESTSIDE SERVICING

Print one per hoist.
Keep it at the controls.

DAILY HOIST PRE-USE CHECK

HOIST / BAY _____ WEEK STARTING _____ CHECKED BY _____

CHECK	MON	TUE	WED	THU	FRI	SAT
1. CLEAR THE BAY No people, tools, hoses or oil under or around the hoist. Floor dry and clean.	☐	☐	☐	☐	☐	☐
2. ARMS & PADS Pads in place and not torn or worn through. Arm restraints lock when the arms are set.	☐	☐	☐	☐	☐	☐
3. SAFETY LOCKS Listen for the locks clicking as it rises. Lower onto the locks before anyone works underneath.	☐	☐	☐	☐	☐	☐
4. CABLES, CHAINS & HOSES No fraying, kinks, flat spots or hydraulic oil leaks.	☐	☐	☐	☐	☐	☐
5. CONTROLS Up, down and stop all work. No jerky movement, grinding or new noises.	☐	☐	☐	☐	☐	☐
6. BASE & ANCHORS No cracks in the slab around the base plates. Anchor bolts in place, tight and rust-free.	☐	☐	☐	☐	☐	☐
7. THE LOAD Within the hoist's rated capacity. Use the manufacturer's lift points, especially on EVs. Check the car is balanced before full lift.	☐	☐	☐	☐	☐	☐

FOUND A PROBLEM?

Don't use the hoist. Lower any vehicle only if it's safe to, isolate the power, tag it OUT OF SERVICE and tell your supervisor. Then call Westside Servicing on 0405 475 078.

Pre-use checks are done by the operator. Routine, annual and 10-year major inspections must be done by a competent person (AS 2550.9:2024). Always follow your hoist manufacturer's manual. This checklist is a general guide.